

# Kesmac Floating Head Fairway – Transportable Reel Mower

## SPECIFICATIONS

SPECIFICATIONS								
GANG	5 GANG		7 GANG		9 GANG		11	
WIDTH OF CUT	11' - 6"	3505 mm	16' - 0"	4877 mm	20' - 6"	6250 mm	25' - 0"	7620 mm
HEIGHT OF CUT	1/2"-3 1/4"	13-83 mm	1/2"-3 1/4"	13-83 mm	1/2"-3 1/4"	13-83 mm	1/2"-3 1/4"	13-83 mm
WEIGHT	1972 lbs.	0895 Kg.	3035 lbs.	1377 Kg.	3345 lbs.	1518 Kg.	4710 lbs.	2136 Kg.
TRANSPORT HEIGHT	58"	1270 mm	79"	2005 mm	82"	2083 mm	106"	2692 mm
TRANSPORT WIDTH	96"	2415 mm	112"	2795 mm	112"	2845 mm	112"	2845 mm
LENGTH WITHOUT TONGUE	85"	2160 mm	85"	2160 mm	85"	2160 mm	85"	2160 mm
LENGTH WITH TONGUE	136"	3455 mm	136"	3455 mm	136"	3455 mm	136"	3455 mm
TIRES - MAIN FRAME	24 x 12.00 - 12		24 x 12.00 - 12		23 x 12.50 - 12		23 x 12.50 - 12 CASTER 15/600x6	
TIRES - WING FRAME	18 x 8.5 - 8		18 x 8.5 - 8		18 x 8.5 - 8		18 x 8.5 - 8	
DRIVE	PTO & V BELTS		PTO & V BELTS		PTO & V BELTS		PTO & V BELTS	
CUTTING REELS	7.88" DIA. x 30" 200 mm DIA.x762 mm		7.88" DIA. x 30" 200 mm DIA.x762 mm		7.88" DIA. x 30" 200 mm DIA.x762 mm		7.88" DIA. x 30" 200 mm DIA.x762 mm	

## STANDARD MODEL

### Benefits

- Scissor-like cut is better for your turf
- Light weight, less compaction
- Low horsepower required
- Mows up to 160 acres per day, 11 Gang or 130 acres per day, 9 Gang

## UPGRADES

### Advanced Reel Design with Single Point Adjustment



- Reel adjustment with one single knob
- Hand control and lock
- Heavy duty bed knife holder
- Available on all Kesmac Fairway Mowers