

Brouwer RoboMax John Deere Sod Harvester

SPECIFICATIONS

Increased production up to 1600 sq. yds (1340 m³) R/HR
 Utilizes a standard tractor
 Short wheelbase, compact turning.
 Extra large flat lug radial flotation tires, ideal for on turf and soft conditions.
 Very easy to operate and maintain, with all main functions at your fingertip.
 Has a quiet, roomy and most comfortable cab that offers excellent visibility and full view of all operations.

Tractor Specifications: John Deere 6105M/6115M (Europe)

John Deere.....6105M / 6115M (Europe)
 Power.....6105M - 105 HP, 6115M - 115 HP
 Cab.....ComfortView Premium
 Front Tires.....400/55-225 Flotation
 Rear Tires.....650/55-R26.5 Flotation Radial
 Transmission.....24 Speed AutoQuad PLUS

Harvester Specifications:

Width of Cut.....16" (406 mm), 23" (584 mm), 24" (610 mm)
 Thickness of Cut.....Hydraulics Adjustable to 3" (76 mm)
 Pallets.....1.2m x 1.2m, 1 m x 1.2 m & 0.8 m x 1.2 m pallet
 Cutting Blades.....Standard
 Weight..D/S Pallet Injector - 24 in. Conveyor: 22420 lbs. (10170 kg.)
 Weight....S/S Pallet Injector - 16 in. Conveyor: 21517 lbs. (9760 kg.)
 Width.....170" (4318 mm)
 Length.....294" (7468 mm)
 Height.....112" (2845 mm)
 Transport Width.....140" (3556 mm)

UPGRADES

Double Sided Pallet Injector

Brush Kit

Spare Parts Kit